


LMWL - 1

CDM-T 70-150W Up & Down Wall Light - IP65

A range of architectural wall luminaires, Lumitron's LMWL-1, is specifically offers an excellent integration with any kind of internal furniture and exterior facades. Direct (downward) / indirect (upward) emission provides elegant appearance, aesthetically suitable for prestigious projects. Ideal solution for both interior and exterior lighting, such as historical and commercial building, main entrance areas, arenas, conventional halls, structural pillars, columns, and outdoor facades.

Specifications

- Housing: corrosion resistant die cast aluminium body and faceplate.
- UV-stabilized polyester powder coat finish in White RAL 9003, or Black RAL 9005. Other color available on request.
- Reflector: high purity, anodized aluminium reflector with choices of beam angle:
 - ☐ A: down light 125° (One way)
 - ☐ B : down light 125° + up light 27°
 - ☐ C : down light 45° + up light 45°
 - ☐ D : down light 27° + up light 27°
- Diffuser: heat-resistant, safety tempered glass lens.
- Stainless steel screws.
- Sturdy and vandal resistant construction.
- Durable silicone rubber gasket.
- Lampholder: G12 base, ceramic type, VDE approved.
- Built-in control gear: accommodates ballast, ignitor, and P.F. correction capacitor. Lumitron offers only anti-cycling, super-imposed ignitor to avoid ballast failures during ends of lamp life.
- IP 65 Vandal resistant, dust-tight and water-jetproof.
- Conforming to DIN, VDE, IEC Class I Electrical.



Ordering Information

| Lumitron Ref. | Lamp Type | Lumen | Color Temp. | Base | Remark |
|----------------|-----------|-------|--------------|------|----------------------------------|
| LMWL-1-35CDM-T | CDM-T 35W | 3,300 | 3,000K | G12 | Recheck lumen with lamp catalog. |
| LMWL-1-70CDM-T | CDM-T 70W | 6,600 | 3,000-4,200K | G12 | |