



## LMWL - 2

### 70-150W Up & Down Wall Light IP65

A range of architectural wall luminaires, Lumitron's LMWL-2, is specifically offers an excellent integration with any kind of internal furniture and exterior facades. Direct (downward) / indirect (upward) emission provides elegant appearance, aesthetically suitable for prestigious projects. Ideal solution for both interior and exterior lighting, such as historical and commercial building, main entrance areas, arenas, conventional halls, structural pillars, columns, and outdoor facades.

#### Specifications

- Housing: corrosion resistant die cast aluminium body.
- Colour: UV resistant polyester powder coat, resistance to salt spray. Finish in White RAL 9010, Black RAL 9005, or silver aluminium color.
- Reflector: high purity anodized 99.85% aluminium reflector chemically brighten.
- Diffuser: heat-resistant, safety tempered glass lens.
- Stainless steel screws.
- Durable silicone rubber gasket.
- Control Gear: built-in type, accommodates ballast, ignitor, lampholders VDE approved, and P.F. correction capacitors. Electronic ballast version available on request for compact size.
- Lumitron offers only anti-cycling ignitor, super-posed versions to avoid ballast failures during ends of lamp life.
- IP 65 dust-tight, and jet-proof. Conforming to EN60598-1, DIN, VDE, IEC Class I Electrical.
- Installation/Mounting: wall or column mounting.



#### Ordering Information

Lumitron Ref.	Lamp Type	Lumen	Color Temp (K)	Base	Remark
LMWL-2-70HPS-DE	HPS-DE 70W	6,800	2,000	RX7s	Recheck lumen with lamp catalog.
LMWL-2-150HPS-DE	HPS-DE 150W	15,000	2,000	RX7s	
LMWL-2-70MH-DE	MH-DE 70W	5,200	3,000-4,200	RX7s	
LMWL-2-150MH-DE	MH-DE 150W	11,250	3,000-4,200	RX7s	