



LMDL - 63

MR16 Halogen Recessed Downlight

Applications

 A recessed downlight, Lumitron's LMDL-63, is suitable for low voltage halogen MR16. Ideal for commercial lighting applications, exhibition halls, exclusive residential projects, decorative applications hotels, shopping, arcades, residences, condominiums, department stores, discount stores, and etc.

Specifications

Housing: metal body and trim polyester powder-coated in black.

• Reflector: black baffle reflector.

• Suitable for 12V MR16 20W up to 50W.

• Polyester powder-coating in: (add suffixes to Lumitron Ref.)

□ -WH: White color□ -BK: Black color□ -SL: Silver color

• Lampholder: GX5.3, ceramic type.


• Transformer: magnetic or electronic transformer.

Mounting: recessed mounting by supporting clips and fasteners.

• Diameter 116mm, cut-out 95mm.







Ordering Information

Lumitron Ref.	Lamp Type	Beam Angle	Color Temp.	Base	Remark
LMDL-63-20MR16	MR16 20W	10°-40°	3,000°K	GX5.3	
LMDL-63-35MR16	MR16 35W	10°-40°	3,000°K	GX5.3	
LMDL-63-50MR16	MR16 50W	10°-40°	3,000°K	GX5.3	