


## LMDL - 133

### Wall Washer Recessed Downlight

LUMITRON:LMDL-133



#### Applications

- A range of aesthetically-pleasing design, recessed fixed-position downlight, horizontal lamp direction. Lumitron's LMDL-133, is specially design for bathroom, damp area, dusty areas, suitable for PLC, and MH lamp to provide sufficient light output where medium to high ceiling height installation is required. Ideal for commercial lighting applications, exhibition halls, exclusive residential projects, shopping arcades, hotels, condominiums, and etc.

#### Specifications

- Suitable for twin compact fluorescent PLC 18-26W, and single MH 70-150W.
- Reflector: high purity, mirror anodized aluminium chemically brighten.
- Diffuser: thermal shock, frosted safety tempered glass lens.
- Housing: steel with white polyester powder coated or galvanized without paint for superior corrosion resistance.
- Trim: die cast aluminium trim with polyester powder coating white finish.
- Lampholders: G24d-2, G24d-3, RX7S base.
- Gearbox (for HID only, not required for incandescent and halogen lamps): remote gearbox accommodates ballast, ignitor, and P.F. correction capacitor. Lumitron offers only anti-cycling, super-posed ignitor to avoid ballast failures during ends of lamp life.
- Mounting: recessed mounting by employing supporting tools and locking devices.
- Cut-out diameter 207x178mm.

#### Ordering Information

Lumitron Ref.	Lamp Type	Lumen	Color Temp.	Base	Remark
LMDL-133-218PLC	PLC 2x18W	2x1,200	2,700-4,000K	G24d-2	
LMDL-133-226PLC	PLC 2x26W	2x1,800	2,700-4,000K	G24d-3	
LMDL-133-70MH	MH 70W	5,500	3,200-4,000K	RX7s	
LMDL-133-150MH	MH 150W	11,250	3,200-4,000K	RX7s	