

# LMDS - 10

## Surface Downlight

### Applications

- A range of surface-mounted downlights specially designed for high wattage compact fluorescent lamp. Applicable for low to high ceiling installations upon light source. Lumitron's LMDS-10, is ideal for commercial lighting applications, plazas, shopping arcades, hotels, restaurants, condominiums, atrium areas, under canopy, corridors, and walkways.

### Specifications


- Suitable for twin compact fluorescent PLE 2x15-23W, PLC 2x18, PLC 2x26W.
- Housing: metal housing, finish in white or black polyester powder coating.
- Trim: die-cast aluminium white polyester powder coating.
- Reflector: high purity, mirror anodized aluminium chemically brighten.
- Diffuser: heat resistant, safety tempered glass.
- Lampholders: PLE and G24d.
- Installations: surface mounting.
- IP42
- Applicable for pendant rod-mounting.



LUMITRON



LUMITRON



LUMITRON REF.	Lamp	Lumen	Base
LMDS-10-PLE	PLE 2x15-23W	2x900-1,550	E27
LMDS-10-218PLC	PLC 2x18W	2x1,200	G24d
LMDS-10-226PLC	PLC 2x26W	2x1,800	G24d
LMDS-10-32PLT	PLT 2x32W	2x2400	GX24q