


## LMUL - 9, LMUL - 10

Architectural buried inground designed for decorative amenity applications such as public areas, commercial and residential areas I.e hotels, homes, and condominiums. Lumitron's LMUL-9, LMUL-10 is applicable for halogen light source, including MR16, PAR30 and PAR38 lamps. Ideal for terraces, corridors, walkways, columns, trees, walls, columns, entrances, and facades.


### Specifications

- Housing: corrosion resistant aluminium body.


- Finish in black. Other color available on request.
- Heat resistant, clear tempered safety glass diffuser.
- Sealed with silicone gaskets.
- Stainless steel screws and fasteners.
- IP 66 dust tight and downpours proof.
- Class I Electrical conforming to DIN, VDE, IEC.



**LMUL-9A**




**LMUL-9B**




**LMUL-9C**


Lumitron Ref.	Lamp Type	Beam Angle	Base	Remark
LMUL-9A LMUL-9B LMUL-9C	MR16 50W	10°-40°	GX5.3	Remote Transformer



**LMUL-10A**



**LMUL-10B**



**LMUL-10C**

Lumitron Ref.	Lamp Type	Beam Angle	Base	Remark
	HAL PAR38 100W	12°, 30°	E27	
LMUL-10A	PAR38 120W	12°, 30°	E27	With Aluminium Reflector
LMUL-10B	PAR30 75W	10°, 30°	E27	
LMUL-10C	PAR30 100W	10°, 30°	E27	