


LMDL - 5

Single / Twin Compact Fluorescent Downlight


A functional recessed downlight, horizontal lamp direction. Lumitron's LMDL-5 is suitable for compact fluorescent lamp range from 5W up to 26W, twin lamp. Applicable for dusty and wet area such as bath room, and general areas. Suitable for commercial lighting applications, exclusive residential projects, shopping arcades, hotels, restaurants, condominiums, and etc.

Specification Features


- Suitable for single or twin compact fluorescent PLC 13W, 18W and 26W.
- Reflector: high quality anodized aluminium. Providing wide beam light distribution.
- Trim: corrosion resistant, die cast aluminium trim with polyester powder coating white finish..
- Diffuser: frosted glass.
- Housing: galvanized steel with white polyester powder-coated.
- Gearbox: corrosion resistant, aluminium type.
- Mounting: recessed mounting by employing support clips and screw fastening.
- Lampholders: G24d, E27
- Optional Feature: P.F. correction capacitor.
- Comply to DIN, VDE, and IEC Class I Electrical.




LMDL-5A
Cut-out 120mm



LMDL-5B
Cut-out 150mm



LMDL-5C
Cut-out 178mm



LMDL-5D
Cut-out 215mm

LUMITRON REF.	Dimension Ø	Lamp	Lumen	Base
LMDL-5A	147mm	PLE 5-8W	235-400	E27
LMDL-5B	160mm	PLE 5-11W	235-600	E27
LMDL-5C	190mm	PLE2x18W	2x1,000	E27
		PLC2x13W	2x900	G24d
LMDL-5D	230mm	PLC2x18W	2x1,200	G24d
		PLE 2x23W	2x1,500	E27
		PLC 2x18W	2x1,200	G24d
		PLC 2x26W	2x1,800	G24d