



## **APPLY**


## Up & Down Wall Light IP65

Architectural wall luminaries, Lumitron's Apply, is specifically designed for decorative amenity applications such as public areas, commercial and residential areas. Applicable for various types of light source, including compact fluorescent lamps for energy saving applications. Ideal for terraces, corridors, walkways, columns, trees, entrances, and facades.

## **Specifications**


- Housing: corrosion resistant die cast aluminium body.
- Colour: UV resistant polyester powder coat, resistance to salt spray. Finish in White RAL 9010, Black RAL 9005, or silver aluminium color.
- Diffuser: toughened Prismatic glass lens..
- IP 65 dust-tight, and jet-proof. Conforming to EN60598-1, DIN, VDE, IEC Class I Electrical.
- Installation/Mounting: wall or column mounting.
- Choices of beam direction:
  - ☐ S: single direction beam (Downward)
  - ☐ D: double direction beam (Upward & Downward)











## **Ordering Information**

Lumitron Ref.	Lamp Type	Lumen	Color Temp.	Base	Remarks
APPLY-S APPLY-D	GLS 60W	730	2,700K	E14	Recheck lumen with lamp catalog.
	HAL-DE 200W	3,200	3,000K	R7S	
	PLS 11W	900	2,700-4,000K	G23	
	PLC 26W	1,800	2,700-4,000K	G24d-3	
	PLL 18W	1,200	2,700-4,000K	2G11	