


LMWL - 135


A circular shape, architectural wall luminaire suitable for walls, corridors, building facades, stairwells, walkways, shopping malls, hyper-markets, and other amenity applications. Provide glare-free lighting as the diffuser faces downward for maximum illumination to the walkway. Thanks to its durability, versatility and its stylish circular shape. Lumitron's LMWL-135 Series is specifically designed to incorporate compact fluorescent lamps for energy saving lighting applications.

Specifications


- Housing: corrosion resistant die cast aluminium body.
- UV-stabilized polyester powder coat finish in Black RAL 9005. Other color available on request.
- Stainless Steel front panel
- Diffuser: Opal polycarbonate lens.
- Stainless steel screws and silicone rubber gasket.
- Lampholder: E27, G24d-1 VDE approved.
- Built-in control gear.
- IP 55 Vandal resistant construction, dust-proof and jet-proof.
- Conforming to DIN, VDE, IEC Class I Electrical.



LMWL-135A



LMWL-135B



LMWL-135C

Ordering Information

Lumitron Ref.	Lamp Type	Lumen	Color Temp.	Base	Remark
LMWL-135A LMWL-135B LMWL-135C	GLS 60W	730	2,700K	E27	Recheck lumen with lamp catalog.
	PLE 15W	900	2,700-4,000K	E27	
	PLS 7W	400	2,700-4,000K	G23	
	PLS 9W	600	2,700-4,000K	G23	
	PLC 13W	900	2,700-4,000K	G24d-1	
	PLC 18W	1,200	2,700-4,000K	G24d-2	
	PLC 26W	1,800	2,700-4,000K	G24d-3	