trident



MGRIVEN

>trident CYM I50

	AD3302	TRIDENT CYM 150	OUTDOOR USE
	AD3303	TRIDENT CYM 150 HFT	OUTDOOR USE



The ultra compact TRIDENT CYM 150 gives high efficiency but low energy use. The high IP66 rating against water and dust ingress means that the unit is suitable for virtually any exterior or interior application and can be mounted in any orientation. The colour mixing system with cyan, yellow and magenta dichroic filters creates virtually unlimited colour hues, coupled with smooth blends between colour changes.

AD3216 BARNDOOR

AD3218

LP0999

CDM-SA/T 150W LAMP

FIXING PLATE

ACCESSORIES



AD3227 EXPANSION FILTER



AD3307 WIDE OUTPUT FILTER



AD4110 IP65 UNIVERSAL DMX CONTROLLER



AD4118 POWER CDI COMMANDER



AD4119 POWER CDI COMMANDER PLUS



AD4120 RADIO SIGNAL RECEIVER



AD4122 RADIO SIGNAL TRANSMITTER



AD4124 RADIO SIGNAL REPEATER

TECHNICAL SPECIFICATIONS

Metal Halide lamp CDM-SA/T 150, 150W, 12.900 lm, 4.200 K

Average rated life 6.000 hours, G12 base (ordering code LP0999) OPTICAL GROUP

The optical system utilises an aluminium ellipsoidal reflector and produces a soft edge beam of approximately 20°

Optional filters are available for alternative beam adjustments

22°x54° expansion filter (ordering code AD3227) 32° wide output filter (ordering code AD3307)

COLOUR CHANGER SYSTEM

CYM colour changer system operated by six high precision step motors, whereby the mixing of cyan, yellow and magenta dichroic filters can create virtually any desired colour

A simulation of black-out effect is achieved by the simultaneous closing of all dichroic filters, which is controlled from an external DMX controller.

On-board dip-switch panel for digital data assignment and stand alone operation control Eight pre-set selectable colour sequences and blends

Master and Slave

3 channels of standard DMX 512
Test mode for troubleshooting operation

HFT version with wireless DMX receiver

Wireless DMX control system (ordering code AD4120, AD4122, AD4124)

IP65 universal DMX controller for full remote programmable control (ordering

code AD4110)

Programming software with USB compatible download IP65 box (ordering code AD4118) Enhanced programming software with USB compatible download IP65 box (ordering code AD4119)

ELECTRICAL SPECIFICATIONS

Power supply:

200-220 / 230-250V / 50-60Hz / 1.1A @ 230V

Power consumption: 200W

3,15 Amp fuse protection

Electrical class: I Meets CE safety standards

Pressure diecast aluminium body, with an adjustable mounting yoke

Scratch resistant polyester grey finish, which protects against UV deterioration

and general corrosion

Front tempered glass shock resistant


Convection cooling plus an internal axial fan keep the level of heat within the unit constant and help dissipation through the body

Certified IP66 protection rating

Shock resistance: 0,8J

WEIGHT

15.6 kg



PHOTOMETRIC DIAGRAMS

AD3302

AD3303


AD3302+AD3307

AD3303+AD3307

AD3302+AD3227 AD3303+AD3227



--- CO / C180 ---- C90 / C270 cd / 1000 lm




Total Flux 6285 Im Maximum 2703 cd/Klm

Total Flux 6597 Im

Maximum 6334.51 cd/kl














Total Flux 5171 Im Maximum 2545.90 cd/Klm

--- CO / C180 cd / 1000 lm

trident

