


# LED Downlight

- Polycarbonate and aluminium body
- Anodized aluminium reflector
- Input Voltage: 220VAC
- Option:
  - Frosted PMMA Diffuser



Frosted PMMA Diffuser

## ITDL - 109




LED 5W  
 3,000K (400-440 Lm)  
 4,000K (420-462 Lm)  
 6,000K (440-484 Lm)

Replacement **MR16 35W**

Energy Saving **75%**

Payback **6 Months**

## ITDL - 110




LED 10W  
 3,000K (800-880 Lm)  
 4,000K (840-924 Lm)  
 6,000K (880-968 Lm)

Replacement **MR16 50W**

Energy Saving **80%**

Payback **1 Year**

## ITDL - 111




LED 10W  
 3,000K (800-880 Lm)  
 4,000K (840-924 Lm)  
 6,000K (880-968 Lm)

Replacement **MR16 50W**

Energy Saving **80%**

Payback **1 Year**

## ITDL - 112



LED 15W  
 3,000K (1,000-1,100 Lm)  
 4,000K (1,100-1,210 Lm)  
 6,000K (1,200-1,320 Lm)

Replacement **PAR30 75W**

Energy Saving **80%**

Payback **1 Year**

LED 20W  
 3,000K (1,600-1,760 Lm)  
 4,000K (1,680-1,848 Lm)  
 6,000K (1,760-1,936 Lm)

Replacement **PAR30 100W**

Energy Saving **80%**

Payback **6 Months**

LED 30W  
 3,000K (2,400-2,640 Lm)  
 4,000K (2,520-2,772 Lm)  
 6,000K (2,640-2,904 Lm)

Replacement **PAR38 120W**

Energy Saving **85%**

Payback **6 Months**

LED