# ITFL - 56
## LED Floodlight Luminaires







**ITFL-56-BM**

**ITFL-56-UB**

Die Cast Aluminium Body | Safety Tempered Glass | 90-265 VAC | 50/60Hz Frequency Range | DMX512 Control Mode | -25°C +40°C Ambient Temperature | IP66 | ENERGY SAVING

6° 15° 25° 40°

White | Warm White | Red | Green | Blue | Yellow | RGB

Option:

| LUMITRON REF. | ITFL-56-24L-43W | ITFL-56-24L-67W | ITFL-56-36L-65W | ITFL-56-36L-95W |
|---|---|---|---|---|
| LED Quantity | 24Pcs | 24Pcs | 36Pcs | 36Pcs |
| LED Power | LED 43W | LED 67W | LED 65W | LED 95W |
| Input Voltage | AC90-265V | AC90-265V | AC90-265V | AC90-265V |
| Frequency Range | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| Color | RGB/Single | RGB/Single | RGB/Single | RGB/Single |
| Beam Angle | 10º, 15º, 25º, 40º | 10º, 15º, 25º, 40º | 10º, 15º, 25º, 40º | 10º, 15º, 25º, 40º |
| Control Mode | DMX512/CC | DMX512/CC | DMX512/CC | DMX512/CC |
| Protection Grade | IP66 | IP66 | IP66 | IP66 |
| Ambient Temperature | -25ºC ~ 40ºC | -25ºC ~ 40ºC | -25ºC ~ 40ºC | -25ºC ~ 40ºC |
| Mounting | Suitable for wall and ground mounting | | | |

LED



* รายละเอียดทางเทคนิคอาจเปลี่ยนแปลงได้โดยไม่ต้องแจ้งให้ทราบล่วงหน้า